

Xerox[®] WorkCentre[®] 7970i Colour Multifunction Printer

The WorkCentre 7970i Colour Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **www.connectkey.com**



System Specifications	WorkCentre 7970i	
Speed		
Colour / Black and white	Up to 70 / 70 ppm	
Monthly Duty Cycle ¹	Up to 300,000 pages	
Recommended Average Monthly Print Volume ²	10,000 to 40,000 pages	
Hard Drive / Processor / Memory	Minimum 250 GB HDD / 1.2 GHz Dual-core / 2 GB system plus 1 GB page memory	
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct with Optional Xerox® USB Wireless Adapter	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning	
Optional Controller	EFI™ Fiery® Network Server	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 2400 dpi	
First-print-out Time Colour / Black and white	As fast as 6.9 seconds / 4.2 seconds	
Page Description Languages	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)	
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bidirectional Real-time Status, Scaling, Job Monitoring, Xerox® Colour By Words, Application Defaults, Two-sided Printing (as default), Hold All Jobs	
Mobile Printing and Apps	Standard: Apple® AirPrint™, Mopria Certified, QR Code App, Xerox App Gallery App, @PrintByXerox App; Free Download: Xerox® Print Service Plug-in for Android, Mopria™ Print Service Plug-in for Android™, Xerox® Mobile Link App; Optional: Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service	
Scan		
Standard Features	Destinations: Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A	
Optional Features	ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional	
Fax		
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement	
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)	
Security		
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions	
Optional Features	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software	
Accounting		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®	

Control Panel Languages				
	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic			
Accessories	·			
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Horizontal Transport Kit BR Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (Recommended use with optional Work Surface) EFI™ Fiery® Network Server Smart Card Enablement Kit Walk up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Acces	5 Device, this is an interface to th	ird party access control devices, such a	s coin machines and card readers.
Electrical Requirements				
	Voltage: 220-240 VAC +/- 109 Frequency: 50/60 Hz +/- 3%,			
Power Consumption				
Running (Average)	1005 watts			
Standby Mode	116 watts			
Low Power Mode	94 watts			
Auto Off / Sleep mode	3.5 watts (Default time to Sleep mode = 2 mins)			
Warm-up	Time from power off to when services are displayed: As fast as 169 seconds			
Low Power Recovery	As fast as 4 seconds			
Operating Environment				
Required Temperature Range	10° to 28° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels (Base Configuration)	Operating 7.6 LwAd (B), Standby: 3.5 LwAd (B)			
Sound Pressure Levels (Base Configuration)	Operating: 58.0 LpAd (dBA), S	tandby: 17.0 LpAd (dBA)		
Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration	640 mm	699 mm	1,149.2 mm	151.9 kg
Base Configuration with BR Finisher	1,302 mm	699 mm	1,149.2 mm	195.6 kg
Base Configuration with BR Booklet Maker Finisher	1,431.4 mm	699 mm	1,149.2 mm	212.3 kg
Base Configuration with BR Booklet Maker Finisher and C Fold / Z Fold Unit	1,664.2 mm	726 mm	1,149.2 mm	264.4 kg
Base Configuration with BR Booklet Maker Finisher, C Fold / Z Fold Unit and High Capacity Feeder	1,978.2 mm	726 mm	1,149.2 mm	297.5 kg
Certifications				
	TUV Listed to "UL 60950-1, Se TUV Certified to "CSA 22.2 No CB Certified / CE Marked (IEC ENERGY STAR® Version 2.0 Common Criteria (IEEE 2600.) EAC NOM Ukraine Apple® AirPrint™ 1.4 Certificati Mopria™ Certified Wi-Fi Direct Certification Blue Angel ECOLOGO® EPEAT (United States) GS Mark Cerner	. 60950-1-07, Second Edition" 60950-1, Second Edition) 2 standard) (undergoing evaluati		

Paper Handling	
Duplex Automatic Document Feed	
Capacity ³	130 sheets (Single-pass DADF)
Speed	up to 80 images per minute black and white and colour (simplex) / up to 133 images per minute black and white and colour (duplex)
Paper Sizes Sensed	A5 to A3
Weights	60 to 128 g/m ²
Bypass Tray	
Capacity ³	100 sheets
Sizes	Custom sizes: 89 x 98 mm to 320 x 483 mm
Weights	60 to 300 g/m ²
Types	Bond Card Stock, Card Stock Reloaded Custom Envelopes Glossy Card Stock, Glossy Card Stock Reloaded Heavyweight Card Stock, Heavyweight Card Stock Reloaded, Heavyweight Glossy Card Stock, Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight, Lightweight Card Stock, Lightweight Card Stock Reloaded, Lightweight Glossy Card Stock, Lightweight Glossy Card Stock Reloaded Plain, Plain Reloaded Preprinted Recycled Transparencies
Trays 1 and 2	
Capacity ³	520 sheets each
Sizes	Tray 1: Custom sizes: 140 x 182 mm to 297 x 432 mm short edge feed (SEF) Tray 2: Custom sizes: 140 x 182 mm to SRA3 (SEF)
Weights	60 to 256 g/m ²
Types	Bond Card Stock, Card Stock Reloaded Custom Envelopes Glossy Card Stock, Glossy Card Stock Reloaded Heavyweight Card Stock, Heavyweight Card Stock Reloaded, Heavyweight Glossy Card Stock, Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight, Lightweight Card Stock, Lightweight Card Stock Reloaded, Lightweight Glossy Card Stock, Lightweight Glossy Card Stock Reloaded Plain, Plain Reloaded Preprinted Recycled Transparencies
High Capacity Tandem Tray (Total	
Capacity ³	Tray 3: 867 sheets Tray 4: 1,133 sheets
Sizes	Standard Sizes: A4
Weights	60 to 256 g/m²
Types	Bond Card Stock Custom Glossy Card Stock Hole punched Labels Letterhead Lightweight Card Stock, Lightweight Glossy Card Stock Plain Preprinted
High Capacity Feeder (HCF) (Optio	nal)
Capacity ³	2000 sheets
Sizes	Standard Sizes: A4, B5 LEF
Weights	60 to 256 g/m²
Envelope Tray (Optional–Replaces	Τταγ 1)
Capacity ³	Up to 60 envelopes
Sizes	DL, C5 Custom sizes: 98 x 148 mm to 162 x 241 mm
Weights	75 to 90 g/m ²

Total Capacity		
Device Total Capacity ³	5,140 sheets	
Finishing		
Output Trays (Standard)		
Stacking Trays ³	Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets	
Optional BR Finisher (Requires		
Capacity ³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) A3 or 200 sets (single-position staple) A4	
Sizes	A6 to A3 for stacking B5 to A3 for stapling	
Weights	60 to 300 g/m² (coated and uncoated)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 g/m² A3, A4, B4 and B5 sizes supported	
Hole Punch	2-4 Hole Punch 4 Hole Swedish Punch (Optional)	
Optional BR Booklet Maker Fin	isher (Requires Horizontal Transport Kit)	
Capacity ³	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4 / A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3	
Sizes	A6 to A3 for stacking B5 to A3 for stapling	
Weights	60 to 300 g/m² (coated and uncoated)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 g/m² A3, A4, B4 and B5 sizes supported	
Hole Punch	2-4 Hole Punch 4 Hole Swedish Punch (Optional)	
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 g/m ² coated or 5 sheets at 177 to 220 g/m ² coated) Bi-fold up to 5 sheets A3, A4 supported	
C Fold / Z Fold Unit (Optional w	vith BR Finisher and BR Booklet Maker Finisher)	
Types	C Fold, Z Fold and Z Half Fold	
Capacity ³	40 sheets	
Sizes	C Fold and Z Fold: A4 SEF only Z Half Fold: A3 only	
Weights	64 to 90 g/m ²	
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold	
Convenience Stapler (Optional	- Recommended with Optional Work Surface)	
Capacity ³	50-sheet stapling 5,000 staples Requires a separate outlet	
Сору		
First-copy-out Time (A4-size, from Platen to Centre Tray) (Colour / Black and white)	As fast as 7.3 seconds / As fast as 5 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1	
Quantity	1 to 9,999	
Resolution (max.)	Up to 600 x 600 dpi	
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)	

Copy Features	Annotation and Bates [™] stamping (with colour capability and font size adjustment) Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tay Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Colour Stapling Transparencies	
	PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com	
Print		
Print Resolution	Up to 1200 x 2400 dpi	
Print Features	Application Defaults	
Print from LISB	Anner Sheet Enable / DisableBidirectional StatusCustom Colour Options (Colour By Words)Cover SelectionDelay Print (specific time)User PermissionsImage Options (Toner Saver, Resolution (Standard, Enhanced, High)Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)Layout / WatermarkN-up (up to 16 pages per sheet)Booklet layoutFinishingFit to new paper sizeHold All JobsPaper Selection by AttributeLAN Fax (requires optional Fax Kit)Sample SetSaved Job (colour jobs can be printed as monochrome)Secure Print with Timed DeletionSpecial Pages (exception page programming: covers, inserts, exception pages)Store and Recall Driver SettingsSustainability Features (Xerox* Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)Two-sided Printing (as default)	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS ⁴ , PCL Colour jobs can be printed as black and white	
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	

Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / AirPrint™ IPv6 Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox [®] Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft [®] Office [®] rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.	
Xerox® Mobile Link App (Free at Google Play Store and Apple® App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.	
Unified Address Book for Fax, Inte	ernet Fax, Email and Scan to	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 133 ipm colour scanning, up to 133 ipm black and white – A4 LEF	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)	
Maximum Scan Area	A3	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression—single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A	
Document Management Fields (Meta Data)	 Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations Customised fields viewed on user interface for variable data input 	

Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)	
Scan to Email (Standard)		
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email Signing (requires Smart Card option) Auto send to self	
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilises the Unified Address Book	
Scan to (Standard)		
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)	
Network Scanning – Software Solu	tions	
Xerox® Scan to PC Desktop® Professional (Optional)	 A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: PaperPort Professional image viewing and file management software Complete PDF functionality Secure PDF workflow of all scanning applications OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability 	
Xerox® ConnectKey® for DocuShare® (optional)	Xerox [®] ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.	
Security		
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted Password Protected PDF (Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite / Securely delete jobs using approved algorithms On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Primissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec Identity Services Engine (ISE) integration, Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation) 	
Xerox® PrintSafe Software (Optional)	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.	
Fax		
Fax Network Server Fax Features Compatibility	ITU (CCITT) group 3	
Network Server Fax Features Compatibility	Various Xerox Alliance Partner Solutions	
Network Server Fax Features		

Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		
Internet Fax Features			
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients		
Directory Access	Utilises the Unified Address Book		
Send / Receive	Multi-page TIFF, Image only PDF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)		
Network Protocols	SMTP (send), POP3 (receive)		
Compliance	ITU-T T.37 compliant		
Walk-up Fax Features (Optional (C	Customer-installable) – 1 and 2 lines)		
Compatibility	ITU (CCITT) Group 3		
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilising T38 (optional)		
Compression / Speed	MH/G3, MMR/SG3		
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report		
Directory Access	Utilises the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals		
Auto Resend	Up to 5 attempts		
Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2		
Xerox [®] CentreWαre [®] Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and assemanagement. Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher. CentreWare Integration available for Tivoli® NetView[®], Unicentre TNG[®], Microsoft Management Console (MMC), HP[®] OpenView[®] 		
Novell NDPS/NEPS	Server gateway application: centralised management tool.		
Xerox® Device Manager	 Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities 		

Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Services – Int	regrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS ⁴ , TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese, Arabic		
Remote Print Services			
Automatic Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replacement (ASR)	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).		
Accounting			
Xerox® Standard Accounting (Stan	dard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file 		
Accounting Options – Network Acc	ounting (Allows central server to manage all accounting)		
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 		
EFI [™] Fiery [®] Network Server (Optio	nal)		
Processor	2.9 GHz, Intel® Pentium® G850 Dual-Core		
Memory (ESS)	1 GB 500 GB HDD		
System Disk Print Languages (PDL)	PostScript v 3020		
Features	PostScript V 3020 Fiery Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Colour Tables Expert Colour Settings: Profile, Rendering and Simulation Fiery FreeForm – Variable Data capabilities Booklet Maker – booklet wizard to create booklets Print from USB flash drive Secure Erase EFI PrintMe Fiery® VUE Calibration Secure Printing User Authentication Drag and Drop job Management with CWS Importing Jobs		
	Detailed Specifications 9		

Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet		
Optional	Fiery Options Bundle (Spot On, Auto Trapping, Hot Folders, Virtual Printers) Network Switch to connect both printer and Fiery Server to Network		
Supplies			
Toner Cartridges (Sold) ^s	Black	26,000 pages	006R01513
	Cyan	15,000 pages	006R01516
	Magenta	15,000 pages	006R01515
	Yellow	15,000 pages	006R01514
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064
Staple Cartridges	for BR Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	for BR Booklet Maker Finisher (1 cartridge per carton)	5,000 each cartridge	008R13177
Staple Refills	for BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
Xerox® Smart Kit®			·
Drum Cartridge ⁶	1 Cartridge per Colour	125,000	013R00662
Waste Toner Container ⁷	1 Cartridge	43,000	008R13061

² Expected regular monthly throughput.

³ Paper capacities are based on 75 g/m² stock; capacities will vary with different weight stocks.

⁴ XPS option is required to print XPS files.

⁵ Assumptions: Toner cartridge yield is based on 5% area coverage on A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set points.

⁶ Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 30% colour / 70% black and white pages.

⁷Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.



©2016 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, Mobile Express Driver®, Scan to PC Desktop®, SmartKit® and WorkCentre® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 3/16 BR10519 W79SS-01EC