Xerox® AltaLink® Multifunction Printer



B8045/B8055/B8065/B8075/B8090

AltaLink B8000 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



System Specification	AltaLink B8045	AltaLink B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090		
Simplex Speed							
A4 (LEF)	45 ppm	55 ppm	65 ppm	75 ppm	90 ppm		
A4 to B4 (SEF)	36 ppm	36 ppm	49 ppm	49 ppm	54 ppm		
A3 (A3 SEF)	31 ppm	31 ppm	42 ppm	42 ppm	47 ppm		
(Bypass Tray will reduce speed by 10 to 20%)							
Auto Duplex Speed							
A4 (LEF)	Up to 45 ppm	Up to 55 ppm	Up to 65 ppm	Up to 75 ppm	Up to 87 ppm		
	(22.5 sheets)	(32.5 sheets)	(32.5 sheets)	(37.5 sheets)	(43 sheets)		
Monthly Duty Cycle ¹	Up to 175,000 pages / month	Up to 200,000 pages / month	Up to 250,000 pages / month	Up to 300,000 pages / month	Up to 400,000 pages / month		
Recommended Average Monthly Print Volume ²	15,000 to 75,000 pages	20,000 to 100,000 pages	25,000 to 110,000 pages	30,000 to 125,000 pages	50,000 to 150,000 pages		
Hard Drive / Processor / Memory	Minimum 250 GB HDD / 1.8 GHz Quad-Core / 4 GB system memory						
Connectivity	Ethernet 10/100/1000 Base-1	Γ, High-speed USB 2.0 direct pr	int, Wi-Fi Direct with optional X	erox® USB Wireless Adapter, NI	-C Tap-to-Pair		
Controller Features	Unified Address Book, Remote	Unified Address Book, Remote Control Panel, Configuration Cloning,					
Copy and Print							
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200, 256 shades of gray						
First-Print-Out Time (Ready to print from warmed-up state)	As fast as 3.9 seconds						
First-Copy-Out Time (Ready to copy from warmed-up state)	As fast as 3.8 seconds from the Platen / 7.4 seconds from the Duplex Automatic Document Feeder As fast as 2.9 seconds from the Platen / 6.9 seconds from the Duplex Automatic Document Feeder						
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)						
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs						
Mobile (Optional)							
Mobile Printing	Xerox® Mobile Print, Xerox® M	Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Print Management and Mobility Suite					
Mobile Printing Connectivity	Apple® AirPrint®, Mopria® Cert	ified, Mopria® Print Service Plug	g-in for Android™, @PrintByXero	ox, Xerox® Print Service Plug-in f	or Android™		

Mobile (Optional) Mobile Apps and Xerox® App Gallery Xerox® Print Management	Productivity Apps: Xerox® E Device Management Apps Scan Apps: Xerox® Scanning	asy Translator Service :: QR Code	gle Drive®, Microsoft® OneDrive	e®, Microsoft Office 365™, DropB	ox™ and Box®		
App Gallery Xerox® Print Management	Cloud Connector Apps: Prin Productivity Apps: Xerox® E Device Management Apps Scan Apps: Xerox® Scanning	asy Translator Service :: QR Code	gle Drive®, Microsoft® OneDrive	e®, Microsoft Office 365™, DropE	ox™ and Box®		
		able in the Xerox® App Gal	llery at www.xerox.com/appg	gallery.			
and Mobility Suite, Xerox® Print Management & Mobility Service	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.						
Scan							
Standard Features		Destinations: Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A					
Optional Features	ConnectKey® for DocuShare®	, other solutions available	e through various Xerox Busine	ess Innovation Partners			
Fax							
Standard Features	Internet Fax, Fax Build Job, N	Network Server Fax Enable	ement				
Optional Features	Fax Forward to Email or SMB	, Walk-up Fax (one-line an	nd two-line options, includes LA	AN Fax)			
Security							
Standard Features	Authentication, Common Cri	iteria Certification (ISO 15		Encryption (FIPS 140-2 complic), Encrypted Secure Print, Secure	int), SHA-256 Hash Message Fax, Secure Scan, Secure Email,		
Optional Features	McAfee Integrity Control, Sm	nart Card Enablement Kit	(CAC/PIV/.NET)				
Accounting							
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement						
Optional Features	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners						
Device Specification							
Control Panel Languages			n, Italian, German, Internation an, Romanian, Catalan, Arabic		iguese, Swedish, Norwegian, Danish,		
Accessories							
Optional	HCF Kit (A3 SEF) (HCF requir Envelope Tray (Replaces Tray Office Finisher (optional with	red) (SEF Kit available for Ey 2) n B8045/B8055/B8065/B8 Maker (optional with B804 rer (optional with B8045/B8 nal with B8065/B8075, rer ooklet Maker (optional wit I with High Volume Finishe ral with High Volume Finish es Work Surface) re options, includes LAN Forerox® USB Wireless Adapte	8075 only) 45/B8055/B8065/B8075 only) 8055/B8065/B8075 only) quired for B8090) th B8065/B8075/B8090) er with Booklet Maker) sher with Booklet Maker)				
Foreign Device Interface (FDI)	Also known as Auxiliary Acce	ess Device, this is an interfo	ace to third party access contr	ol devices, such as coin machine	es and card readers.		
Electrical Requirements							
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5% 16 A						
Power Consumption	AltaLink B8045	AltaLink B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090		
Running (Average)	1,150 watts	1,250 watts	1,550 watts	1,600 watts	1,650 watts		
	45 watts	45 watts	310 watts	310 watts	310 watts		
Standby Mode	4 watts						
Standby Mode Low Power Mode	4 watts						
-	4 watts ≤4 watts (Default time to sle	ep = 1 minutes)					
Low Power Mode		ep = 1 minutes)					

Operating Environment						
Required Temperature Range	10 to 32° C					
Required Reletive Humidity	15% to 85%					
Sound Power Levels	Operating: 7.1 B(A); Standby 5.0 B(A)	Operating: 7.2 B(A); Standby 5.0 B(A)	Operating: 7.3 B(A); Standby 5.0 B(A)			
Sound Pressure Levels	Operating 56 dB(A), Standby 35 dB(A)	Operating 57 dB(A), Standby 35 dB(A)	Operating 58 dB(A), Standby 35 dB(A)			
Dimensions and Weight						
Base Configuration with OCT	Width: 850 mm Depth: 665 mm Height: 1,150 mm Weight: 113 kg					
With Office Finisher (B8045/B8055/B8065/B8075 only)	Width: 1,470 mm Depth: 665 mm Height: 1,150 mm Weight: 142.5 kg					
With Office Finisher with Booklet Maker (B8045/B8055/B8065/ B8075 only)	Width: 1,530 mm Depth: 665 mm Height: 1,150 mm Weight: 158.5 kg					
With High Volume Finisher and High Capacity Feeder (B8065/B8075/B8090 only)	Width: 2,135 mm Depth: 665 mm Height: 1,150 mm Weight: 139 kg					
With High Volume Finisher with Booklet Maker, Z Fold / C Fold Unit, Post Process Inserter) and High Capacity Feeder (B8065/B8075/B8090 only)	Width: 2,485 mm Depth: 665 mm Height: 1,150 mm Weight: 196.5 kg					
High Capacity Feeder	Width: 1,995 mm Depth: 510 mm Height: 510 mm Weight: 30 kg					
Work Surface (Does not add to overall width if combined with High Capacity Feeder)	Width: 285 mm					

System Certification/Regul	atory Compliance
System Certification/Regul Certifications	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) (B Certified (IEC 60950-1, Second Edition) GS Apple® AirPrint® 1.6 Certification Blue Angel* Citrix Certified Common Criteria (IEEE 600.2 standard)* WHQL SAP IPv6 Mopria® v1.2 Certified Google Cloud Print® Cerner® MEDITECH 508 Compliance Bonjour Conformance FIPS 140-2 Open SSL McAfee® CC mark ENERGY STAP® 2.0 ECOLOGO® EPEAT® (Gold - B8065/B8075B/8090 only; B8045/B8055 undergoing evaluation) EU ERP LOT4 EAC Russla UKRESPRO Ukraine BIS (India) ADA 508
	NRTL mark (CB certified) 4 Nordic safety statements Nordic Swan (B8000 series meets requirements) CAN ICES 003 (A) NMB-3A
	Wi-Fi WI-Fi Direct WEEE NOM RoHS
D 11 11	*In progress, refer to latest on-line product specifications document at www.xerox.com/AltalinkB8000Specs.

Paper Handling AltaLink B8045 AltaLink B8055 AltaLink B8065 AltaLink B8075 AltaLink B8096 Single-Pass Duplex Automatic Document Feeder (DADF) Capacity 200 sheets Speed Up to 140 images per minute (ipm) colour (simplex) Up to 200 ipm black and white (duplex) Paper Sizes Sensed 125 x 138 mm to 297 x 432 mm Weights So to 160 gsm Bypass Tray Capacity 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2 Capacity 500 sheets each									
Capacity' 200 sheets Speed Up to 140 images per minute (ipm) colour (simplex) Up to 200 ipm black and white (duplex) Paper Sizes Sensed 125 x 138 mm to 297 x 432 mm Weights 50 to 160 gsm Bypass Tray Capacity' 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carboniess Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Paper Handling	AltaLink B8045	AltaLink B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090			
Speed Up to 140 images per minute (ipm) colour (simplex) Up to 200 ipm black and white (duplex) Paper Sizes Sensed 125 x 138 mm to 297 x 432 mm Weights 50 to 160 gsm Bypass Tray Capacity' 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Single-Pass Duplex Automa	matic Document Feeder (DADF)							
Up to 200 ipm black and white (duplex) Paper Sizes Sensed 125 x 138 mm to 297 x 432 mm Weights 50 to 160 gsm Bypass Tray Capacity³ 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Platin Preprinted Recycled Transparencies Trays 1 and 2	Capacity ³	200 sheets							
Weights 50 to 160 gsm Bypass Tray Capacity³ 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Speed								
Bypass Tray Capacity³ 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Paper Sizes Sensed	125 x 138 mm to 297 x	432 mm						
Capacity³ 100 sheets Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Weights	50 to 160 gsm							
Sizes Custom Sizes: A6 x A3 Weights 60 to 216 gsm Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Bypass Tray								
Weights 60 to 216 gsm Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Capacity ³	100 sheets							
Media Types Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Sizes	Custom Sizes: A6 x A3							
Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Trays 1 and 2	Weights	60 to 216 gsm							
	Media Types	Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled							
Capacity ³ 500 sheets each	Trays 1 and 2								
	Capacity ³	500 sheets each							
Sizes Custom Sizes: A5 to A3	Sizes	Custom Sizes: A5 to A3							
Weights 60 to 200 gsm	Weights	60 to 200 gsm							

- 1 12	- Boo 13/Boo33/Boo03/Boo7 3/Boo30 Water an edion 1 Times
Trays 1 and 2	
Media Types High Capacity Tandem Tray	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Cardstock Plain Preprinted Recycled Transparencies (Tray 2 only)
Capacity ³	Tray 3: 1,600 sheets
	Tray 4: 2,000 sheets each
Sizes	A4
Weights	60 to 216 gsm
Mediα Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Cardstock Plain Preprinted Recycled
Envelope Tray (Optional - R	teplaces Tray 2)
Capacity ³	Up to 50 envelopes
Sizes	Monarch, DL, C5
Weights	75 to 90 gsm
High Capacity Feeder (HCF) (Optional)
Capacity ³	3,300 sheets Optional HCF Kits: 1,250 sheets with A4/Legal HCF Kit or 1,250 sheets with A3 SEF HCF Kit (Optional) (SEF Kit available for B8065/B8095 only)
Sizes	A4 LEF Optional HCF Kits: A4 or A3 (SEF Kit available for B8065/B8075/B8090 only)
Weights	60 to 216 gsm
Media Types	Bond Card Stock Hole punched Index Letterhead Plain Preprinted Recycled
Total Capacity	
Device Total Capacity ³	8,000 sheets
Finishing	AltaLink B8045 AltaLink B8055 AltaLink B8065 AltaLink B8075 AltaLink B8090
Offset Catch Tray (OCT) (O	ptional with B8045/B8055/B8065/B8075) (Required when finisher not attached)
Capacity	Up to 400 sheets of 80 gsm
Office Finisher (Optional w	ith B8045/B8055/B8065/B8075 only)
Top Tray Capacity	250 sheets unstapled of 80 gsm
Stacking Tray Capacity	2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)
Top Tray Sizes	A6 to A3
Stacking Tray Sizes	A5 to A3
Weights	60 to 216 gsm
Multiposition Stapling	50 sheets of 80 gsm
Hole Punch (Optional) Europe	2-4 Hole Punch

	boo is/booss/booss/booss/booss/ witelfulletion i mitel
Office Finisher with Booklet	t Maker (Optional with B8045/B8055/B8065/B8075 only)
Top Tray Capacity	250 sheets unstapled of 80 gsm
Stacking Tray Capacity	2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)
Top Tray Sizes	A6 to A3
Stacking Tray Sizes	A5 to A3
Weights	60 to 216 gsm
Multiposition Stapling	50 sheets of 80 gsm
Hole Punch (Optional)	
Europe	2-4 Hole Punch
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 80 gsm or less)
Booklet Making Sizes	A4 SEF B4 SEF A3 SEF
Saddle-Stitch Stapling	2-15 sheets / 8-60 page booklet 60 to 90 gsm
Folding (unstapled)	1-5 sheets / unstapled
High Volume Finisher (HVF)) (Optional with B8065/B8075, required for B8090)
Top Tray Capacity ³	250 sheets
Stacking Tray Capacity ³	3,000 sheets
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	60 to 216 gsm
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional) Europe	2-hole punch 4-hole punch and 4-hole "Swedish" punch (Optional with B8065/B8075, required for B8090)
High Volume Finisher with	Booklet Maker (Optional with B8065/B8075/B8090)
Top Tray Capacity ³	250 sheets
Stacking Tray Capacity ³	3,000 sheets
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	60 to 216 gsm
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional)	
Europe	2-hole punch 4-hole punch and 4-hole "Swedish" punch
Booklet Making Capacity ³	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited
Booklet Making Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm
Booklet Maker Weights	60 to 216 gsm
Saddle-Stitch Stapling ³	Saddle-Stitch (2-15 sheets / 8-60 page booklet)
Folding	V-folding (1-5 sheets / unstapled)
Z Fold / C Fold Unit (Option	al with HVF with Booklet Maker)
Capacity ³	50 sheets or unlimited capacity with try stop in down position
Sizes	A4 / 210 x 297 mm
Weights	60 to 216 gsm
Post Process Inserter (Option	onal with HVF and HVF with Booklet Maker)
Capacity ³	250 sheets
Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm
Weights	60 to 216 gsm

Convenience Stapler									
Cαpαcity ³	50-sheet stapling 5,000 staples Requires separate power								
Сору	AltaLink B8045	AltaLink B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090				
First-Copy-Out Time	As fast as 3.8 seconds from the Platen / 7.4 seconds from the Duplex Automatic Document Feeder As fast as 2.9 seconds from the Platen / 6.9 seconds from the Duplex Automatic Document Feeder								
Sides (input:output)	1-1, 1-2, 2-2, 2-1								
Quantity	1 to 9,999	1 to 9,999							
Resolution(max)	Up to 600 x 600 dpi								
Reduction/Enlargement	Variable zoom from 25 %	Variable zoom from 25% to 400% in 1% increments.							
Concurrency	Program-ahead to allow	job to be initiated while initial job	is processed (Copy, Print,	Fax and Scan)					
	Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings								
Xerox® Copier Assistant®	Xerox® Copier Assistant® attached via the USB por	Transparencies Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied Pt attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy feature Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com.							
Print	AltaLink B8045	AltaLink B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090				
First-Page-Out Time	As fast as 3.9 seconds								
Resolution	Up to 1200 x 1200, 256	shades of gray							
Print Features	Job Identification (Print I LAN Fax (requires option Layout / Watermark N-up (up to 16 pages per Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attrib Sample Set Saved Job Secure Print with Timed I Special Pages (exception Store and Recall Driver Se	status aver, Resolution (Standard, Enhand ID or Banner, Print ID in margins of al Fax Kit) r sheet) ute Deletion page programming: covers, inserectings	on first page only or all pa						
	Two-sided Printing (as de	Kerox® Earth Smart Settings, Duple	ex, N-up, Turn-off Banner	una riint 10, sinart sample set, i	HOIG All JODS)				

Print	AltaLink B8045 AltaLin	ık B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090
Operating Systems	Microsoft® Windows® XP SP3 (32- and Windows Server 2003 SP2 R2 (32- and Windows Server 2008 and R2 (32- and Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mindows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	l 64-bit)			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Microsoft Windows Networking over If Bonjour® / AirPrint® IPv6 Secure FTP Most protocols not in use can be disab	P	Raw Socket Printing/Port 9	100, IPv4/IPv6, WSD	
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HT	TTPS, DHCP Autone	et, TLS, NTP, MDNS		
Font Capability	PCL: 93 scalable fonts, line printer and	bitmap font (inclu	ding Cyrillic font support) Po	ostScript 3: 173 Type 1 fonts, 2 N	Multiple Master fonts
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, u Driver automatically discovers availabl application print settings for use on an	le printers and prov	vides status and capability i	nformation. Save a list of "favori	
Xerox® Global Print Driver®	A truly universal print driver that lets IT consistent, easy-to-use interface for en		. 13		3 1
Xerox® Pull Print Driver	Makes it easy for IT managers to quali single driver. The Xerox® Pull Print Drive configure multiple drivers. Used in con	er extends conveni	ence across a broad range o	of printing assets. IT administrat	
Unified Address Book for Fo	x, Internet Fax, Email and Scan to				
Features	Services supported: Fax, Internet Fax, E Maximum contacts: 5,000 Contacts: Supports 1 or more destinati Favorites for quick access of all services	ions			
Scan	AltaLink B8045 AltaLin	ık B8055	AltaLink B8065	AltaLink B8075	AltaLink B8090
Concurrency	Scan while the system is printing, copy concurrent jobs)	ring, or while it is tr	ansferring scan to network (or fax jobs (priority is for return o	f scanned originals and printing
Input Speed	Up to 140 images per minute (ipm) (si Up to 200 ipm (duplex) black and whit				
Resolution	72 x 72 dpi to 600 x 600 dpi				
Bit Depth	1-bit (black and white), 8-bit (greyscale	e), 24-bit (colour)			
Maximum Scan Area	A3				
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan ter	nplates and share	via device cloning to other	multifunction printers Confirmat	ion sheet options
Network Filing Protocol	sFTP, FTP, SMB, HTTP, HTTPS				
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPE Black and white TIFF (G3MH, G4 MMR Searchable PDF/OCR and PDF/A-1b (M MRC)) Linearised PDF / PDF/A	compression - sin		BIG Arithmetic Compression, Del	Flate (for Black and white and within
Document Management Fields (Metadata)	Features only available in Network Sca • 1 to 6 user programmable metadata field name, default value and other a • Customised fields viewed on user int	a fields per network configurations	scan to file templates and	unlimited fields within the temp	late – Metadata field consists of
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, The Control of Size of Size (For Mixed Size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)		per / Magazine)		

ACIOX AILULIIIK	D0043/D0033/D0003/D0073/D0030 Widthunction Filliter
Scan to Email (Standard)	
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)
Scan to (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries) Scan to Home Scan to USB Scan to Network Scan to Email
Workflow Scanning (Option	oal)
Scanning Software	Autostore v7 ecopy ShareScan v5.2 eCopy ScanStation v5.2
Scanning Apps and Xerox® App Gallery	Scan to/from: Dropbox™, Google Drive™, Microsoft® OneDrive®, Microsoft Office 365™ and Box® See the full list of apps available in the App Gallery: www.xerox.com/appgallery.
Security	AltaLink B8045 AltaLink B8055 AltaLink B8065 AltaLink B8075 AltaLink B8090
	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2008), Windows Server 2008, SMB (Windows Server 2008), SMB (Windows Server 2008), SMB (Windows Server 2008), SMB (Windows Server 2008), Windows Server 2008, SMB (Windows Server 2008), SMB (Windows Server 2008), Windows Server 2008, SMB (Windows Server 2008), NET Expertable Securety (Securety Access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation)
Fax	AltaLink B8045 AltaLink B8055 AltaLink B8065 AltaLink B8075 AltaLink B8090
Network Server Fax Feature	us s
Compatibility	ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	A3
Send Features	One- or Two-sided Scanning (up to A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)
Print Fax Features	One- or Two-sided Printing, Staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Compatibility	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilises the Unified Address Book
Send/Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi, Bit Depth: 1-bit (black and white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features	
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional)

Walk-up Fax Features	
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilises the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
Xerox® Embedded Web Serv	ver - Integrated Device Web Page
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)

Browsers	Allows simple, remote installation setting of configuratio Internet Explorer 7.x, 8.x, 9.x	n options and management of the device	
	Internet Explorer 7.x, 8.x, 9.x		
	Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available vi	a web page	
	International English, International French, Italian, Germ Russian, Simplified Chinese, Korean, Japanese, Arabic	an, International Spanish, Dutch, Brazilian Portuguese, Swa	edish, Norwegian, Danish, Finnish,
Remote Services			
	Automates the process of collecting and submitting met time-consumingend-user involvement and ensures that r	er reads for tracking and billing of Xerox® device usage. Elir neter reads are submitted to Xerox on time.	ninates the need for
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices I	pased on actual usage, eliminating the need to manually m	nanage supplies inventory.
	Offers a fast (and free) way to resolve potential issues ar to Xerox®, allowing for problems to be solved faster with	d receive assistance and automate the troubleshooting/reincreased uptime.	pair process. Diagnostic data is sen
Accounting			
Xerox® Standard Accounting	(Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group accounts (Department)		
	 Administrator can manage the feature via the Web Us Administrator has the ability to import or export user or 	er Interface or device control panel in tools. ccounts, Group Accounts, General Accounts and User limit:	s via an industry standard CSV file.
Accounting Options – Netwo	rk Accounting (Allows central server to manage all a	counting)	
	 Numerous solutions are available through Xerox Allian Security enhancements with the addition of HTTPS pro 	cking and reporting of device usage of copy, print, scan and ce Partners. For details visit www.xerox.com otocol support ty server enabling larger databases of users and accounts to third party Networking Account	1 server fax
Supplies De	escription	Quantity	Part Number

Supplies	Description	Quantity	Part Number
Supplies			
Toner Cartridge	Includes 2 Toner Cartridges	100,000 pages (50,000 pages each) ⁶	006R01604
Staple Cartridges	Office Finisher (B8045/B8055/B8065/B8075 only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker (B8045/B8055/B8065/B8075 only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker – saddle-stitch stapling (B8045/B8055/B8065/B8075 only)	2,000 per cartridge (8,000 staples)	108R01158
	HVF and HVF with Booklet Maker (B8065/B8075/B8090 only) • Complete Cartridge • Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12912 008R12898
	HVF with Booklet Maker – saddle-stitch stapling (B8065/B8075/B8090 only)	2,000 per cartridge (16,000 staples)	008R12897
	Convenience Stapler Complete Cartridge Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941
Drum Cartridge		Up to 200,000 ⁵	013R00675

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
² Expected regular monthly throughput.
³ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
⁶ Average standard pages. Declared in accordance with ISO/IEC 19752. 88K Yield will vary based on media size, image area, coverage, Print Mode, media orientation and usage patterns.
⁵ 200,000 yield will vary depending on job length, media size/orientation and machine speed.



